

Bradyprinter™ Models 1244 and 1344



Printers are available in either 203 dpi or 300 dpi print resolution.



Models 1244 and 1344 are available with optional media stand.

The Bradyprinter models 1244 and 1344 are small, compact and economical. Featuring print resolutions of either 203 dpi or 300 dpi and a wide print width of 4.100", the 1244 and 1344 printers are ideal for general purpose product identification, wire and cable marking and laboratory identification.

For small to medium volume printing, the Bradyprinter models 1244 and 1344 provide all the power and quality you need for on-demand in-house printing. The moveable transmissive sensor allows the use of all Brady stock configurations in a variety of materials including polyester, paper, vinyl and sleeves.

Bradyprinter Model 1244

Part Number	Description
BP-1244	Brady Model 1244

Model 1244 Specifications

Print resolution	203 dots per inch (8 dots per mm)
Print speeds	Selectable print speeds at 1" increments from 2.000" (50.80 mm) to 4.000" (101.60 mm) per second
Minimum label length	0.250" (6.35 mm)

Bradyprinter Model 1344

Part Number	Description
BP-1344	Brady Model 1344

Model 1344 Specifications

Print resolution	300 dots per inch (12 dots per mm)
Print speeds	Selectable print speeds at 1" increments from 2.000" (50.80 mm) to 4.000" (101.60 mm) per second
Minimum label length	0.250" (6.35 mm)

Bradyprinter Models 1244 & 1344 Field-Installable Options

Part Number	Description
BP-12/13-3MB-FLASH	1244/1344 3MB memory expansion+H4
BP-12/13-REALCLOCK	1244/1344 internal clock option
BP-12/13-CUTTER	1244/1344 standard cutter option
BP-12/13-LD-CUTTER	1244/1344 light duty cutter option
BP-12/13-KEYBOARD	1244/1344 keyboard
BP-12/13-MS	1244/1344 media stand
BP-12/13-PRESSENSR	1244/1344 present sensor option

Ribbons

- ▶ 361' (110m) length
- ▶ Recommended to be as wide as media
- ▶ 0.500" core

Programming Language

- ▶ DPL selectable through software or easy-to-use control panel with user programmable password

Fonts (standard)

- ▶ Bitmap fonts A through H and GS symbols
- ▶ Scalable font CG Triumvirate™ Bold Condensed (4 pts.-36 pts.)
- ▶ IBM® Code Page 850 multilingual character set

Electrical

- ▶ Universal power supply with power-factor correction 90-264 VAC, 48-62 Hz

Electronics

- ▶ 32-bit microprocessor
- ▶ 2 MB RAM memory
- ▶ 1 MB flash

Bar Codes/Symbologies

- ▶ All popular symbologies including:
Linear bar codes: Code 11, Code 39, Code 93, Code 128 with subsets A/B/C and UCC Case Codes, ISBT-128, UPC-A, UPC-E, EAN-8, EAN-13, UPC and EAN 2 or 5 digit extensions, Plessey, Postnet, Standard 2 of 5, Industrial 2 of 5, Interleaved 2 of 5, LOGMARS, MSI, Codabar
2-dimensional bar codes: Codablock, PDF-417, Code 49, DataMatrix, Maxi Code, Micro-PDF, QR Code

Physical

- ▶ Height: 6.000" (152.42 mm)
- ▶ Width: 8.500" (215.90 mm)
- ▶ Depth: 9.500" (241.30 mm)
- ▶ Weight without options: 5.2lbs. (24kg) printer only

Communications Interfaces

- ▶ Serial and parallel interfaces standard
- ▶ High speed parallel interface, Centronics® compatible

Environment

- ▶ Operating temperature: 40° to 95°F (5° to 35°C)
- ▶ Storage/Transportation: -40° to 140°F (-40° to 60°C)
- ▶ 20% to 85% Non-condensing R.H.

Options

- ▶ Label peel (full roll liner rewind)
- ▶ Additional options available



**Identification Solutions
& Specialty Tapes**

www.bradyid.com

WORLDWIDE LOCATIONS

Australia 1-800-620-816
Belgium 32-(0)-152-457-811
Brazil 55-11-3686-4720
Canada 1-800-263-6179
China (Beijing) 86-10-6517-1260
China (Shanghai) 86-21-5255-0008
China (Wuxi) 86-510-528-2222
England 44-(0)-1295-228-200

France 00-33-1-69-29-67-00
Germany 49-(0)-607-196-03
Hong Kong 852-2359-3149
Italy 39-02-967-00-507
Japan 81-45-461-3600
Korea 82-2-400-8418
Latin America 1-414-540-5560
Malaysia 60-4-283-3980

Mexico 525-399-6963
New Zealand 61-2-8717-2200
Philippines 632-658-2077
Singapore 65-775-2077
Sweden 46-(0)-859-005-730
Taiwan 88-(6)-2-2345-1430
Thailand 66-2-943-0777
U.S.A. 1-800-537-8791